

Digital tank contents indicator DTA 10



- For fuel oil EL, L, diesel fuel, biodiesel, water and other media with a density from 0.5 to 1.5 g/cm³
- Universal application in tanks of a height of up to 4 m
- Push-to-Read function:
Fast start with just a push of a button



Application Location-independent level measurement with digital display and minimum level signal (reserve level alarm) with a single measurement. Suitable for tanks up to 400 cm liquid level. For fuel oil EL, L or diesel fuel, FAME 100 % as biodiesel (EN 14214) and water (no drinking water!). In addition, DTA 10 can be used for level measurement with all non-corrosive liquids with a density from 0.5 to 1.5 g/cm³. Remote measurements up to 15 m.

Description The electro-pneumatic tank contents indicator DTA 10 consists of a battery-operated control unit with digital display and a measuring line. Measured values are displayed in litres, % and liquid level (cm). Simple operation and setup via three function keys. Measurements are requested by means of pressing the control key (Push-to-Read function). If the level falls below a minimum level that is freely adjustable as a percentage, the backlight of the display flashes red to indicate an alarm during the measurement. Standard tank shapes (linear, spherical, cylindrical and horizontal) are stored. Measuring line connection for hose with 4 mm inside diameter.

Technical data

Functions

Push-to-Read level measurement

Measuring range (tank height)

0/400 cm (fuel oil)

0/350 cm (water)

Measuring accuracy

±3.0 cm

Operating temperature range

Ambient: 0/50 °C

Storage: -20/+65 °C

Medium: 0/50 °C

Display

Multi-coloured, backlit graphical display (30 x 50 mm):

- Blue = Operation
- Red = Alarm
- Green = Setup

Indication of litres (5 digits),

% or liquid level in cm

Measuring line

PVC hose 4 x 1 mm

Length 20 m

Balance chamber stainless steel

Supply voltage

9 V monobloc battery

Visual alarm

Backlight flashes red during measurement process

Housing

Wall mounting housing made of impact-resistant plastic (ABS)

W x H x D: 100 x 188 x 65 mm

Degree of protection: IP 20 (EN 60529)

Scope of delivery

- Control unit
- 9 V monobloc battery
- 20 m measuring line with balance chamber
- Connection kit for G1/2, G1, G1 1/2 and G2
- 25 x nail cable clips, 2 x hose clamps
- Hose adapter (4 mm)
- Mounting accessories

i

DTA 20 E: Smart Home-enabled version based on Basis EnOcean® wireless see page 98.

DG: M, PG: 4	Part no.	Price €
DTA 10 with Pneumofix	52145	
DTA 10 without Pneumofix	52155	