Checklist for enquiries - thermometers

Company:	Project/enquiry:
Quantity	
Application	
Medium to be measured	
Version	☐ Bimetal thermometer ☐ Gas filled thermometer
Housing diameter	□ 34 □ 40 □ 50 □ 63 □ 80 □ 100 □ 160 □ 250
Range	
Connection position	☐ Bottom ☐ Back ☐ Every angle version
Connection type	□ Plain □ Loose male connection □ Sep. screw-in thermowell □ Loose union nut □ Sep. weld-in thermowell □ Compression fitting, adjustable □ DIN/EN thermowell □ Fixed male connection Neck □ No □ Yesmm
Connection thread	□ G □ NPT □ BSPT □ For welding □ ¼ □ ⅓ □ ½ □ ¾ □ Other:
Stem length	
Mounting for capillary type	☐ Wall bracket ☐ Back flange ☐ 3-hole fixing, panel mounting bezel
Capillary length	
Housing	☐ Plastic ☐ Sheet steel ☐ Stainless steel with push on bezel ☐ Stainless steel with bayonet bezel
Filling	☐ No filling ☐ Glycerine ☐ Silicone oil ☐ Other:
Stem material	☐ Brass ☐ Stainless steel ☐ Other:
Protective pipe material	☐ Brass ☐ Steel ☐ Stainless steel ☐ Other:
Dial	☐ Single scale as per EN ☐ Dual scale: ☐ Special scale: Customer logo ☐ Yes ☐ No
Accuracy class	Class □ 1 □ 2 as per EN 13190
Electrical contacts (only for gas filled thermometers)	□ No □ Magnetic spring contact □ Inductive contact □ Single □ Dual switching function:
Other	



751