Options for magnetic piston pressure gauges/ magnetic diaphragm pressure gauges

DG: M

Туре	MAG 80 Dif, D 312	MAG 100 Dif, D 312	MAG 115 Dif, D 311
Version			
	Available options	Available options	Available options
Maximum static pressure PN 250	•	•	
Maximum static pressure PN 400	•	•	
Centre back connection (electrical contacts not possible)	•	•	
Bottom connection	•	•	
Connection 1/4 NPT female thread	•	•	
Connection G1/4B male thread (adapter)	•	•	
Connection G½B male thread (adapter)	•	•	
Connection 1/2 NPT male thread (adapter)	•	•	
Piston seal FKM (Viton)	•	•	
3-hole fixing, panel mounting bezel (can only be factory-fitted)	•	•	
Window acrylic glass	•	•	•
Window Instrument glass, hardened	•	•	•
Glycerine filling	•	•	
Plus connection right (pointer moves from right to left)	•	•	
Max. pointer	•	•	
Red reference pointer, adjustable	•	•	•
Filter in plus connection	•	•	
Double Reed contact, changeover contact RK2.W (extra charge relates to basic device with single Reed contact, changeover contact RK1.W!)	•	•	
Red / green colour strip	•	•	•
Customer logo, monochrome	•	•	•
Customer logo, bi-colour	•	•	•

Blue part no. = in-stock items

Accessories

DG: M

Туре		MAG 80 Dif, D 312	MAG 100 Dif, D 312	MAG 115 Dif, D 311
	PG	Part no.	Part no.	Part no.
Aluminium mounting plate and fixing clamp for wall mounting or 2" pipe mounting	3	38001	38001	38304
Plastic mounting plate for wall mounting	1	38305	38305	
Mounting kit for MAG 115 Dif. D311 (2 x connection adapter 1/4" NPT x hose connector ø 5 mm grey, 3 x angled brackets, 3 x screws)	1			38334

Blue part no. = in-stock items

11

