

## Sacrificial anodes



### Benefits

- For enamelled boilers or tanks with passive protection layers
- Sacrificial anode with one of the following Ø 22, 26, 33 mm
- With screw fitting G¾, G1 or G1¼
- For improved hygiene: Anode individually packed in poly bag for increased hygiene

### Application

Protection against frequently unnoticed corrosion damage in water heaters. Primarily for use in enamelled boilers or hot water tanks with other types of passive protective coatings. Defective areas in enamel or other passive protective coatings are subject to corrosion; this causes a flow of current which is transformed into a protective current by the anode material. The anode material thus falls victim to electro-chemical corrosion. Since the protective function of the anode rod is not unlimited, consumed anodes have to be replaced.

### Versions

	Part no.
Sacrificial anode 22-500-G¾	69815
Sacrificial anode 22-700-G¾	69817
Sacrificial anode 26-500-G1	69819
Sacrificial anode 26-700-G1	69821
Sacrificial anode 33-550-G1¼	69825

Blue part no. = in-stock items

### Description

Sacrificial anode Ø 22, 26 or 33 mm as per EN 12828, made of magnesium alloy, suitable for all standard tanks. With screw fitting G¾, G1 or G1¼, without signal. See the ordering table for various versions with different lengths, threads and diameters.



## Technical specifications

### Connection

Screw fitting G $\frac{3}{4}$   
Screw fitting G1  
Screw fitting G1 $\frac{1}{4}$

### Design

Rod