



Gas sensor GS 4.1



Benefits

- Additional sensor suitable for gas alarm unit GS 2.1 and gas alarm unit GM 2.1
- Detectable gases: methane or propane / butane
- LEDs indicate the operating and alarm state of the gas alarm system

Application

Additional gas sensor to be used with the gas alarm unit GS 2.1. Enables monitoring at two points in different rooms.

Versions

	Part no.
Gas sensor GS 4.1 Methane	61188
Gas sensor GS 4.1 Propane/butane	61189

Blue part no. = in-stock items

Description

Remote probe for gas alarm unit GS 2.1. Audible alarm is triggered by the gas alarm GS 2.1.

Detectable gases: Methane, butane, propane. LEDs at the sensor indicate the operating and alarm state of the gas alarm system:

LED green: operation

LED yellow: error

LED red: gas alarm



Technical specifications

Supply voltage

Via GS 2.1

Housing

Wall mounting plastic

housing

W x H x D: 80 x 80 x 35 mm

Weight: Approx. 500 g

Degree of protection: IP 20 (EN 60529)

Operating temperature range

Ambient: 0/50 °C

Storage: -10/+60 °C

Humidity/moisture: Max. 75 % r.F.

Alarm value

Approx. 20 % UEG

Service life

Approx. 5 Jahre