

Tank protection package AK-S for fuel oil and diesel



Benefits

- Inner lining package for standardised cylindrical tanks (EN/DIN) with all mounting accessories and vacuum type leak detector Eurovac
- Tank protection packages for rectangular and spherical tanks on request
- Customised training seminars on installation of inner linings and leak detectors possible
- Materials resistant to biofuel and biodiesel mixtures with max. 30 % FAME
- Green fuels ready: suitable for use at tank facilities filed with the new paraffinic fuels HVO or GTL



Application

For fuel oil EL (DIN 51603-1), diesel fuel (EN 590) and biofuel as well as biodiesel with up to 20 % FAME.

Versions

Tank volume	Part no.
3,000 l	43901.003
5,000 l	43901.005
7,000 l	43901.007
10,000 l	43901.010
13,000 l	43901.013
15,000 l	43901.015
16,000 l	43901.016
20,000 l	43901.020
25,000 l	43901.025
30,000 l	43901.030

Blue part no. = in-stock items



Tank volume	Part no.
40,000 l	43901.040
50,000 l	43901.050
60,000 l	43901.060
80,000 l	43901.080
100,000 l	43901.100

Blue part no. = in-stock items

Description

Tank protection package with complete accessories for standardised cylindrical tanks. Enquire for rectangular and spherical tanks.

Technical specifications

Approval

CE as per European Construction Products Regulation ((EU) No 305/2011 and No 574/2014),
EN 13160-1:2003,
EN 13160-7:2003,
DIBt: Z-65.30-162

Scope of delivery

- Leak protection lining according to standard or made to size
- Vacuum type leak detector Eurovac
- Front wall lining made of fleece LSV2
- Intermediate layer made of fleece
- Mipoplast plate 800 x 800 mm
- Condensate bar triple 4/6 mm
- Liquid barrier 4/6 mm
- Angled nipple short 4/6 mm
- Angled nipple long 4/6 mm
- PVC suction line 3 x 6 mm perforated and not perforated
- Fastening ring 500 mm or 600 mm
- Hose connector 4 or 6 mm
- T piece hose connection 4 or 6 mm
- Hose connector kit ND4/6 G $\frac{3}{8}$ x G $\frac{1}{2}$
- Warning sign with holder and felt overshoes